

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
13 October 2005 (13.10.2005)


PCT

(10) International Publication Number
WO 2005/096370 A1

- (51) International Patent Classification⁷: **H01L 21/822**, 27/04, 27/06
- (21) International Application Number: **PCT/JP2005/006550**
- (22) International Filing Date: 29 March 2005 (29.03.2005)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
2004-104136 31 March 2004 (31.03.2004) JP
- (71) Applicant (for all designated States except US): **RICOH COMPANY, LTD.** [JP/JP]; 3-6, Nakamagome 1-chome, Ohta-ku, Tokyo, 1438555 (JP).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **AGARI, Hideki** [JP/JP]; 4-13-207, Jounan 1-chome, Ikeda-shi, Osaka, 5630025 (JP). **YOSHII, Kohji** [JP/JP]; 920-50, Shidehara, Sanda-shi, Hyogo, 6691506 (JP). **OKUDA, Tsugunori** [JP/JP]; 8-22-215, Kouda 3-chome, Ikeda-shi, Osaka, 5630043 (JP).
- (74) Agent: **ITOH, Tadahiko**; 32nd Floor, Yebisu Garden Place Tower, 20-3, Ebisu 4-chome, Shibuya-ku, Tokyo 1506032 (JP).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: A SEMICONDUCTOR APPARATUS



(57) Abstract: A semiconductor apparatus is disclosed. The semiconductor apparatus comprises a substrate with a pad, an internal circuitry region, and a protection resistance formed on the substrate. The pad is connected to a first electrode of the protection resistance by wiring, the internal circuitry region is connected to a second electrode of the protection resistance by wiring, and the protection resistance protects the internal circuitry region from electrostatic discharging. The semiconductor apparatus is characterized in that the pad is placed between the protection resistance and the internal circuitry region.

WO 2005/096370 A1



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.